

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 29 N., R. 33 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T29N R33E $\frac{1}{4}$ $\frac{S \ 2}{S \ 11}$</p> <p style="text-align: center;">1976</p> <p>Descend 20 ft. over a broken S. slope.</p>
51.00	Spur, slopes SSW.; desc. 70 ft. over a broken S. slope.
69.00	Spur, slopes SW.; desc. 340 ft. over a W. slope.
82.44	The cor. of secs. 2, 3, 10 and 11.
	<hr/> <p>N. 0° 43' E., bet. secs. 2 and 3.</p> <p>Over mountainous land, through sagebrush and scattered juniper; asc. 120 ft. over a broken W. slope.</p>
17.00	Spur, slopes W.; asc. 240 ft. over a broken W. slope.
36.30	Spur, slopes W.; desc. 90 ft. over a N. slope.
39.23	<p>The ¼ sec. cor. of secs. 2 and 3, monumented with a mound of stone. No marked stone found. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T29N R33E $\frac{1}{4}$ S 3 S 2</p> <p style="text-align: center;">1976</p> <hr/>
	<p>N. 1° 36' E., beginning new measurement.</p> <p>Over mountainous land; desc. 600 ft. over a N. slope.</p>
19.50	Wash in Rocky Canyon, 30 lks. wide, 1 ft. deep, course W.; asc. 620 ft. over a S. slope.
37.00	Spur, slopes WSW.; desc. 200 ft. over a N. slope.
40.85	The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base to top, mkd. as described in the field notes of T. 30 N., R. 33 E., resurveyed concurrently under this same group.