

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 29 N., R. 33 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T29N R33E $\frac{1}{4}$ S 5 S 4</p> <p style="text-align: center;">1975</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>79.00 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, mkd. as described in the field notes of T. 30 N., R. 33 E., resurveyed concurrently under this same group.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89° 02' W., bet. secs. 8 and 17.</p> <p>Over nearly level land, through shadscale.</p> <p>39.79 Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>CORNER NOT MONUMENTED</p>
	<p>79.58 The cor. of secs. 7, 8, 17 and 18, monumented with the remains of a redwood post, 2 ins. square, 16 ins. long, no scribe marks visible, with a metal tag mkd. 161, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R33E S 7 S 8 S 18 S 17</p> <p style="text-align: center;">1975</p> <p>reset the original wooden post and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>N. 0° 34' E., bet. secs. 7 and 8.</p> <p>Over nearly level land, through shadscale.</p> <p>38.80 Trail road, bears NE. and SW.</p> <p>39.13 Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>CORNER NOT MONUMENTED</p>
	<p>54.80 Ravine, drains WSW.</p>