

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 29 N., R. 33 E., MDM, NEVADA

|  |  |
|--|--|
| CHAINS   |  |
| 47.00  | Rim, bears S. and NNW.   |
| 67.00  | Ravine, drains NE.   |
| 80.19  | The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, mkd. as described in the field notes of T. 29 N., R. 32 E., resurveyed concurrently under this same group.   |
|  | From the cor. of secs. 5, 6, 7 and 8.  |
|  | N. 1° 11' E., bet. secs. 5 and 6.  |
|  | Over nearly level land, through shadscale.   |
| 7.60   | Ravine, drains W.  |
| 39.14  | Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.  |
|  | Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  |
|  | T29N R33E<br>¼<br>S 6   S 5<br><br>1975  |
|  | raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.   |
| 39.30  | Trail road, bears ESE. and WNW.  |
| 78.47  | The cor.. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, mkd. as described in the field notes of T. 30 N., R. 33 E., resurveyed concurrently under this same group. |
| DEPENDENT RESURVEY OF PORTIONS OF M.S. NO. 4678<br>AND M.S. NO. 4632   |  |
| Reestablishment of the Survey Executed by<br>George W. Malone, U.S. Mineral Surveyor,<br>in 1926 and 1929.   |  |
| From the corner of Cor. No. 1 of M.S. No. 4678, Maxwell lode, monumented with a wooden post, 4 ins. square, 4 ft. long, firmly set and exposed 2½ ft. above ground in a mound of stone and plainly scribed MAX-4678-1. |  |