DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 30 N., R. 33 E., MDM, NEVADA

·	T. 30 N., R. 33 E., MDM, NEVADA
CHAINS	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T30N R33E S 31 S 32 S 6 S 5 T29N
	1975
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
	S. 89° 55' W., bet. secs. 6 and 31.
	Over nearly level land, through scattered shadscale.
39.77	Point for the 4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T30N R33E 3 31 S 6 T29N
	1975
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
53.90	Left bank of Humboldt River, bears SSW. and NNE.; across river, course SSW.
55.90	Right bank of Humboldt River, bears SSW. and NNE.
79.54	The cor. of Tps. 29 and 30 N., Rs. 32 and 33 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T30N R32E R33E S 36   S 31 S 1   S 6 T29N
	1975
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.