

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 30 N., R. 33 E., MDM, NEVADA

CHAINS	
	N. 89° 49' W., bet. secs. 6 and 31. Over nearly level land, through scattered shadscale.
35.86	Point selected for the witness corner of secs. 6 and 31. Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.
	W C T31N R33E ¼ ← $\frac{S\ 31}{S\ 6}$ T30N 1975
	set a steel fence post, 6 ft. long, 2¼ ins. in the ground, alongside the iron post.
38.00	Edge of Rye Patch Reservoir, bears N. and S.; across water.
39.97	True point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; falls in Rye Patch Reservoir where corner cannot be perpetuated.
61.00	Edge of Rye Patch Reservoir, bears N. and S.; over level land.
79.94	The cor. of Tps. 30 and 31 N., Rs. 32 and 33 E.
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 30 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA	
Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E. H. Dyer, in 1863, and a Portion of the Survey Executed by U.S. Deputy Surveyor W. H. Craigue, and Transitman N. E. Potter, in 1912, under Group No. 14.	
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 0° 10' W., bet. secs. 34 and 35. Over mountainous land, through scattered shadscale; along broken W. slope.
25.00	Wash, 60 lks. wide, 4 ft. deep, drains W.
27.20	Wash, 150 lks. wide, 20 ft. deep, drains W.
41.94	The ¼ sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set and exposed 20 ins. above ground, with brass cap mkd.