

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 15 N., R. 65 E., MDM, NEVADA

CHAINS	
	Descend 350 ft. over rolling SW. slope.
79.94	The cor. of secs. 3, 4, 9 and 10.
	N. 5° 15' E., bet. secs. 3 and 4.
	Over mountainous land, through medium juniper, pinon, mahogany and sagebrush; desc. 160 ft. over NW. slope.
22.00	Ravine, trail road in bottom, drains SW.; asc. 400 ft. over SW. slope.
38.76	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T15N R65E  <math>\frac{1}{4}</math>  S 4   S 3</p>
	1976
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Ascend 280 ft. over SW. slope.
58.14	Point for the N. 1/16 sec. cor. of secs. 3 and 4, on spur, slopes W.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.
	<p style="text-align: center;">T15N R65E  N1/16  S 4   S 3</p>
	1976
	Descend 190 ft. over NW. slope.
74.51	Intersect the Third Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T16N R65E  S 33  S 4   S 3  T15N   R65E  C C</p>
	1976
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.