DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MDM, NEVADA

CHAINS	
	T15N R65E S1/16 S 5|S 4 1976
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
41.38	The ¼ sec. cor. of secs. 4 and 5, monumented with a mound of stone, steel fence post in center with location tag attached, this is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T15N R65E ¼ S 5|S 4 1976
	set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 24' W., beginning new measurement.
	Over mountainous land; desc. 120 ft. over N. slope.
7.50	Ravine, drains W.; asc. 160 ft. over S. slope.
20.40	Spur, slopes W.; desc. 180 ft. over N. slope.
33.50	Intersect the Third Standard Parallel North.
	Point for the closing cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T16N R65E S 32 S 5|S 4 T15N|R65E C C 1976
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the closing cor., monumented with an iron pipe, 2½ ins. diam., exposed 14 ins. above ground, bears N. 0° 24' W., 0.78 chs. dist., with brass plate on top mkd.