

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 16 N., R. 65 E., MDM, NEVADA

CHAINS		
10.50	Spur, slopes E.; desc. 90 ft. along rolling E. slope to sec. cor.	
20.11	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R64E R65E N 1/16 S 12 S 7</p> <p style="text-align: center;">1975</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 40° E., 4 lks. dist., mkd. N1/16 S7 BT.</p> <p style="padding-left: 40px;">A aspen, 8 ins. diam., bears S. 69 3/4° W., 4 lks. dist., mkd. N1/16 S12 BT.</p>	
40.22	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., exposed 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 17 N., R. 64 E., resurveyed under Group No. 257.	
	<p>N. 0° 03' W., bet. secs. 1 and 6.</p> <p>Over mountainous land, through medium aspen, fir, mahogany and sagebrush; asc. 30 ft. over SE. slope.</p>	
14.80	Ridge, bears NNE. and SSW.; desc. 180 ft. along W. slope.	
44.24	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to cap, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T16N R64E R65E ¼ S 1 S 6</p> <p style="text-align: center;">1975</p> <p>set a steel fence post, 6 ft. long, 18 ins. in the ground, alongside the iron post.</p> <p>Descend 300 ft. over WNW. slope.</p>	
80.00	Sagehen Canyon, trail road in bottom, bears NNE. and SSW.; asc. 30 ft. over ESE. slope.	