DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 10 N., R. 44 E., MDM, NEVADA

		1. 10 N., R. ++ H., IBH
I	CHAINS 14.00	Wash, 30 lks. wide, 2 ft. deep drains W.
	17.70	State Route 92, bears S. $61\frac{1}{2}^{\circ}$ E., to Round Mountain, Nevada; and N. $61\frac{1}{2}^{\circ}$ W., to junction of Nevada State Highway No. 8-A.
	21.40	Telephone line, bears S. 64½° E., and N. 64½° W.
	39.10	Wash, 1 ch. wide, 2 ft. deep, drains W.
	40.15	The 4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2½ ins. diam., exposed 4 ins. above ground, mkd. as described in the field notes of the resurvey of T. 10 N., R. 43 E., under Group No. 384.
		N. 0° 27' E., beginning new measurement.
		Over gently rolling land, through medium undergrowth; shadscale.
	31.10	Wash, 60 lks. wide, 4 ft. deep, drains WNW.
	39.78	The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2½ ins. diam., exposed 4 ins. above ground, mkd. as described in the field notes of the resurvey of T. 10 N., R. 43 E., under Group No. 384.
		DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES T. 10 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA
		Reestablishment of a Portion of the Survey Executed by D.H. Barker, U.S. Deputy Surveyor, in 1874.
	`	The cor. of secs. 9, 10, 15 and 16, monumented with a granite stone, $8x8x4$ ins., plainly mkd. with 4 grooves on S. face and 3 grooves on E. face, and firmly set in a circle of stone.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		TION R44E S 9 S 10 S 16 S 15
		1975
		bury the original cornerstone alongside the iron post and raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.
		N. 89° 55' W., bet. secs. 9 and 16.