Dependent Resurvey, Portion of West Boundary, T. 12 N., R. 38 E., Mount Diablo Mer., Nevada

 	To It is, it so It, notice blable here, hevada
CHAINS	Asc. over SE. slope and enter timber, edge bears E. and W.
62.00	Spur, slopes ESE.; desc. over NE. slope.
76.00	Bottom of descent; asc. over SE. slope.
80.22	The cor. of secs. 13, 18, 19, and 24, monumented with a granite stone, 16 x 10 x 6 ins., firmly set in a mound of stone, $2\frac{1}{2}$ ft. base, 6 ins. high, mkd. with 3 notches on the S. face and 2 notches partially visible on the N. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	T 12 N R 37 E R 38 E S 13 S 18 S 24 S 19 1976
	Bury the mkd. stone alongside the iron post.
	N. 0° 33' W., bet. secs. 13 and 18.
	Asc. over SE. slope, through heavy juniper and pinon pine timber.
35.50	Spur, slopes ESE.; desc. over NE. slope.
39.68	The ½ sec. cor. of secs. 13 and 18, monumented with a granite stone, 24 x 18 x 4 ins., loosely set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with illegible marks on S. face, from which the original bearing tree
	A downed pinon pine, 24 ins. diam., bears N. 63½° E., 67 lks. dist., mkd. S XVIII BT. (Record, N. 60° E., 68 lks. dist.)
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	T 12 N R 37 E R 38 E
	S 13 S 18 1976
	Bury the mkd. stone in the mound of stone.
	Dependent Resurvey of a Portion of the Subdivisional Lines, T. 12 N., R. 38 E., Mount Diablo Meridian, Nevada
	(Restoring the 1881 survey by J. R. Glover and G. H. Perrin)
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.
	N. 0° 02' E., bet. secs. 31 and 32.