

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 12 N., R. 38 E., Mount Diablo Mer., Nevada

CHAINS	
79.78	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp.
Subdivision of Section 31, T. 12 N., R. 38 E., Mount Diablo Meridian, Nevada	
	From the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.
	N. $0^{\circ} 11'$ E., on the N. and S. center line of sec. 31.
	Desc. over gentle NE. slope, through moderate sagebrush.
20.10	Antelope Wash, dry, 15 lks. wide, drains E.; thence over nearly level land.
32.90	Dirt road, 20 lks. wide, bears SE. and NW.
33.10	Dry wash, 20 lks. wide, drains SE.; asc. over SW. slope.
40.10	Point for the center $\frac{1}{4}$ sec. cor. of sec. 31, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 12 N    R 38 E C $\frac{1}{4}$ S 31 1976
51.80	Spur, slopes NW.; desc. over gentle N. slope.
60.16	Point for the center N. $1/16$ sec. cor. of sec. 31.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	C N $1/16$   S 31 C 1976
65.00	Bottom of descent; asc. over gentle SE. slope.
80.22	The $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
	From the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.
	S. $89^{\circ} 56'$ W., on the E. and W. center line of sec. 31.
	Asc. over gentle SE. slope, through scattered juniper and pinon pine and moderate sagebrush.
27.70	Spur, slopes SW.; desc. over SW. slope.
40.30	The center $\frac{1}{4}$ sec. cor. of sec. 31.
	The bottom of descent; thence over nearly level land.
53.60	Dry wash, 20 lks. wide, drains SE.
53.75	Dirt road, 15 lks. wide, bears SE. and NW.; asc. over SE. slope.
60.44	Point for the center W. $1/16$ sec. cor. of sec. 31.