Dependent Resurvey, Portion of South Boundary, T. 12 N., R. 40 E., Mount Diablo Mer., Nevada

	T. 12 N., R. 40 E., Mount Diablo Mer., Nevada
CHAINS	
	From this point the cor. of Tps. 11 and 12 N., Rs. 40 and 41 E., bears S. 89° 42′ E., 236.20 chs. dist., monumented with a granite stone, 34 x 30 x 20 ins., firmly set, protruding 10 ins. above the ground, in a scattered mound of stone, mkd. with 5 grooves on N. and 3 grooves on E. faces; there are no other visible marks.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	T 12 N R 40 E R 41 E S 36 S 31 S 1 S 6 T 11 N 1976
	Bury the original stone and an iron horseshoe alongside the iron post in the mound of stone.
	This control line was fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.
	N. 89° 42' W., bet. secs. 4 and 33.
	Asc. over NE. slope, through moderate juniper, pinon pine, and sagebrush.
2.80	Top of ascent; thence over nearly level land.
19.685	Point for the E. 1/16 sec. cor. of secs. 4 and 33.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	E 1/16 S 33 S 4
39.37	Point for the 4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 12 N R 40 E 1/4 S 33 S 4 T 11 N 1976
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
50.30	Leave nearly level land; desc. over W. slope.
63.75	Indian Creek, 10 1ks. wide, course N. 50° E.; thence over nearly level land.
73.90	Dirt road, 20 lks. wide, bears N. 45° E. and S. 45° W.; thence over rolling hills.