

Dependent Resurvey, Portion of Subdivisional Lines,
T. 13 N., R. 40 E., Mt. Diablo Mer., Nevada

| CHAINS | |
|--------|---|
| | Bury the original stone alongside and raise a mound of stone 2½ ft. base, 1½ ft. high, N. of the cor. |
| | From the cor. of secs. 10, 11, 14, and 15. N. 89° 00' W., bet. secs. 10 and 15. Over rolling hills, through moderate sagebrush. |
| 15.00 | Reese River, 100 lks. wide, course N. |
| 38.60 | Power line, bears N. 30° E. and S. 30° W. |
| 39.16 | Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 13 N R 40 E S 10 ¼ S 15 1975 </div> |
| | Raise a mound of stone, 3½ ft. base, 1½ ft. high, N. of cor. |
| | From this cor. USC & GS triangulation station "Bonita 1954", bears N. 6° 55' E., 19.85 chs. dist. |
| 39.90 | State Hwy. No. 21, dirt, 70 lks. wide, bears N. 30° E. and S. 30° W. |
| 78.32 | The cor. of secs. 9, 10, 15, and 16. |
| | Subdivision of Section 15, T. 13 N., R. 40 E., Mount Diablo Meridian, Nevada |
| | From the ¼ sec. cor. of secs. 15 and 22. N. 1° 31' W., on the N. and S. center line of sec. 15. Over nearly level land, through cultivated field. |
| 19.34 | Point for the center S. 1/16 sec. cor. of sec. 15. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. below the surface of cultivated field, with brass cap mkd. <div style="text-align: center;"> C S 1/16 S 15 C 1975 </div> |
| 20.80 | Barbed wire fence, bears N. 80° E. and S. 80° W.; leave cultivated field. |
| 21.00 | Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. |
| 34.80 | Dirt road, 15 lks. wide, bears N. 60° E. and S. 70° W. |
| 38.68 | Point for the center ¼ sec. cor. of sec. 15, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. |