6

Dependent Resurvey, Portion of Subdivisional Lines, T. 13 N., R. 41 E., Mt. Diablo Mer., Nevada CHAINS N. 0° 31' E., on the E. bdy. of sec. 29. Over rolling hills, through light juniper, pinon and moderate sagebrush. Point for the ¹/₄ sec. cor. of secs. 28 and 29, at propor-38.57 tionate dist.; there is no remaining evidence of the original cor. Set an iron post 28 ins. long, 2¹/₂ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 13 N R 41 E ¹/₄ S 29 | S 28 1977 Point for the cor. of secs. 20, 21, 28, and 29, at propor-77.14 tionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T 13 N R 41 E <u>S 20 | S 21</u> <u>S 29 | S 28</u> 1975 Raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. From this point the cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp. bears N. 1° 08' E., 309.25 chs. dist., monumented with a granite stone, $12 \times 8 \times 6$ ins., firmly set, protruding 6 ins. above the ground, mkd. with 2 grooves on the E. face, with a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, 3 lks. W. of cor. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T 14 N R 41 E S 32 | S 33 S 5 | S 4 T 13 N 1975 Bury the original stone alongside the iron post. This control line was fully retraced and careful search was made for evidence of intervening cors., none of which was recovered. From the cor. of secs. 20, 21, 28, and 29. East, bet. secs. 21 and 28. Over rolling hills, through light juniper, pinon and moderate sagebrush.

40.00

Point for the 1/4 sec. cor. of secs. 21 and 28, at record bearing and dist.; there is no remaining evidence of the original cor.