

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 12 N., R. 61 E., MDM, NEVADA

CHAINS	
	<p>N. 5° 11' W., bet. secs. 7 and 12.</p> <p>Over rolling land, through scattered sagebrush and juniper.</p>
38.48	<p>The ¼ sec. cor. of secs. 7 and 12, monumented with an unmarked limestone, 14x10x3 ins., firmly set in the center of a mound of stone, This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R60E R61E ¼ S 12 S 7</p> <p style="text-align: center;">1975</p> <p>deposit the unmarked stone alongside the iron post.</p>
	<p>N. 4° 05' E., beginning new measurement.</p> <p>Over rolling land.</p>
6.50	<p>Ridge, bears ENE. and WSW.</p>
41.93	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 20x12x10 ins., firmly set in a mound of stone, mkd. with 5 grooves on S. face and 1 groove on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R60E R61E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1975</p> <p>deposit the original cornerstone alongside the iron post.</p>
	<p>N. 2° 34' W., bet. secs. 1 and 6.</p> <p>Over gently rolling land, through scattered sagebrush and juniper.</p>
27.90	<p>Trail road, parallels fence.</p>
28.20	<p>Fence, bears N. 66° E. and S. 66° W.</p>
29.50	<p>Powerline, bears N. 21¼° E. and S. 21¼° W.</p>