## DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 12 N., R. 61 E., MDM, NEVADA

	T. 12 N., R. 61 E., MDM, NEVADA
chains 80.18	The cor. of secs. 11, 12, 13 and 14, monumented with the remains of a squared wooden post, no scribe marks visible, loosely set in a mound of stone, with a steel fence post alongside.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
·	T12N R61E S 11  S 12 S 14  S 13
	1975
	reset the remains of the original wooden post and steel fence post, 5½ ft. long, 22 ins. in the ground, along-side the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	From this corner, the cor. of fences bear N. 56 3/4° E., 0.74 chs. dist., fences bear N. and E.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a spike, in center of paved road, bearing E. and W. This corner is set as described in the field notes of the dependent resurvey of T. 12 N., R. 62 E., surveyed under Group No. 489.
	N. 88° 48' W., bet. secs. 12 and 13.
	Over paved road.
3.00	Paved road, bears E. and NW.; thence along dirt road.
19.20	Paved road, bears N., continue W. along dirt road.
19.60	Powerline, bears N. and S.
40.10	Dirt road, bears N. and S.
40.41	The 4 sec. cor. of secs. 12 and 13, at the cor. of fences bearing N., S. and W. Mrs. Barbara Dennis, owner of adjoining land for 50 years, said this point was the 4 sec. cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.