

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 62 E., MDM, NEVADA

CHAINS	
	<p>The standard cor. of secs. 33 and 34, monumented with a steel fence post, firmly set and exposed 4 ft. above ground and in a mound of stone. No wooden post found. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground to solid rock and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S C T11N R62E <u>S 33 S 34</u></p> <p style="text-align: center;">1975</p> <p>reset the steel fence post alongside the iron post.</p> <p>From this corner a well and pump, bears N. 57½° W., 9.30 chs. dist.</p> <p>N. 88° 40' W., along the S. bdy. of sec. 33.</p> <p>Over gently rolling land, covered with sagebrush and greasewood.</p>
15.40	Head of spring draining WNW., bears N. 2.50 chs. dist.
40.44	<p>Point for the standard ¼ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T11N R62E <u>¼ S 33</u></p> <p style="text-align: center;">1975</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.88	<p>The standard cor. of secs. 32 and 33, monumented with the remains of a squared wooden post, 2x2x36 ins. long, no scribe marks visible, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>