

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF R. 62 E., MDM, NEVADA

CHAINS		
39.81	<p>N. 89° 47' W., along the S. bdy. of sec. 31.</p> <p>Over nearly level land, covered with greasewood.</p> <p>The standard <math>\frac{1}{4}</math> sec. cor. of sec. 31, monumented with a wooden fence post, firmly set and exposed 8 ft. above ground. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T11N R62E <u><math>\frac{1}{4}</math> S 31</u></p> <p style="text-align: center;">1975</p> <p>reset the wooden fence post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/>	
35.36	<p>N. 89° 54' W., beginning new measurement.</p> <p>Over nearly level land, covered with greasewood.</p> <p>The closing cor. of Tps. 10 N., Rs. 61 and 62 E., bears N. .03 chs. dist., monumented with a cedar post, firmly set, showing 7 ft. above ground. Not remonumented.</p>	
41.04	<p>The standard cor. of Tps. 11 N., Rs. 61 and 62 E., determined at the cor. of fences, from which fences bear N., and S. 19<math>\frac{1}{4}</math>° E. This has been recognized as the cor. by adjacent landowners, and is accepted as the best existing evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T11N R61E R62E <u>S 36   S 31</u></p> <p style="text-align: center;">1975 1976</p>	
<p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 11 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p>		
<p>Reestablishment of a Portion of the Survey Executed by E. B. Monroe, U. S. Deputy Surveyor, in 1870.</p> <hr style="width: 20%; margin: auto;"/>		