

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 1 S., R. 50 E., MDM, NEVADA

CHAINS	
40.06	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 18x12x10 ins., mkd. with 1 notch on N. edge and 5 notches on S. edge, firmly set and exposed 8 ins. above ground, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R50E R51E S 1   S 6 S 12   S 7</p> <p style="text-align: center;">1976</p> <p>deposit the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. 0° 01' W., bet. secs. 1 and 6.</p>
	<p>Over rolling land, through medium sagebrush and scattered juniper and pinon; desc. 10 ft. over rolling E. slope.</p>
19.00	<p>Trail road, bears NE. and SW.; desc. 20 ft. over a rolling E. slope.</p>
27.00	<p>Draw, drains NE.; asc. slightly over a rolling E. slope.</p>
40.01	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 15x9x4 ins., mkd. ¼ on W. face, firmly set and exposed 5 ins. above ground, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R50E R51E ¼ S 1   S 6</p> <p style="text-align: center;">1976</p> <p>deposit the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. deep, W. of cor.</p>
	<p>N. 0° 16' E., beginning new measurement.</p>
	<p>Over rolling land; asc. slightly over a rolling E. slope.</p>
1.73	<p>Intersect the Mount Diablo Base Line.</p>