

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASE LINE,
THROUGH R. 42 E., MDM, NEVADA

CHAINS	
40.12	<p>S. 89° 23' E., beginning new measurement.</p> <p>Over gently rolling land; asc. a gradual SW. slope.</p> <p>The standard cor. of secs. 35 and 36, monumented with a volcanic stone, 16x8x2 ins., mkd. with 5 notches on W. edge and 1 notch on E. edge, loosely set alongside a steel fence post, firmly set and exposed 4 ft. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T1N R42E <u>S 35 S 36</u></p> <p style="text-align: center;">1975</p> <p>deposit the original cornerstone and reset the steel fence post, 5 ft. long, 22 ins. in the ground, alongside the iron post.</p>
7.30 17.80 40.15	<p>S. 89° 24' E., along the S. bdy. of sec. 36.</p> <p>Over gently rolling land, through greasewood; asc. a gradual SW. slope.</p> <p>Trail road, bears NNW. and SSE.</p> <p>Trail road, bears NNW. and SSE.</p> <p>The standard ¼ sec. cor. of sec. 36, monumented with a granite stone, 12x8x4 ins., mkd. ¼ on N. face, firmly set in a collar of stone, with a steel fence post firmly set and exposed 4 ft. above ground alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T1N R42E <u>¼ S 36</u></p> <p style="text-align: center;">1976</p> <p>deposit the original cornerstone and reset the steel fence post, 5 ft. long, 20 ins. in the ground, alongside the iron post.</p>
	<p>S. 89° 21' E., beginning new measurement.</p> <p>Over gently rolling land; asc. a gradual SW. slope.</p>