

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASELINE,
THROUGH A PORTION OF R. 47 E., MDM, NEVADA

<p>CHAINS 40.16</p>	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a volcanic stone, 9x5x4 ins., mkd. $\frac{1}{4}$ on N. face, firmly set and exposed 6 ins. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T1N R47E <u>$\frac{1}{4}$ S 36</u></p> <p style="text-align: center;">1976</p> <p>deposit the original cornerstone and set a steel fence post, 5$\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 24' E., beginning new measurement.</p> <p>Over nearly level land.</p>
<p>28.61</p>	<p>Possible closing cor. of Tps. 1 S., Rs. 47 and 48 E., monumented with a mound of stone.</p>
<p>39.94</p>	<p>The standard cor. of Tps. 1 N., Rs. 47 and 48 E., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south bdy. of T. 3 N., R. 48 E., surveyed under Group No. 455 in 1968.</p> <p>From this corner, U.S.C. & G.S. triangulation station "CONTRAVES 12," monumented with a standard bronze disk stamped CONTRAVES 12 1968, firmly set in concrete, bears S. 76° 55' W. mean bearing, 143.46 chs. dist.</p>
<p>DEPENDENT RESURVEY OF THE MOUNT DIABLO BASELINE THROUGH RANGE 48 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor C.F. Putnam, in 1882.</p>	
<p>From the standard cor. of Tps. 1 N., Rs. 47 and 48 E.</p> <p>S. 89° 54' E., along the S. bdy. of sec. 31.</p> <p>Over gently rolling land, through scattered greasewood and sagebrush; asc. 50 ft. over a gradual W. slope.</p>	