

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASELINE,  
THROUGH R. 48 E., MDM, NEVADA

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC TLN R48E <u>S 35   S 36</u></p>
	1976
	deposit the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	S. 89° 47' E., along the S. bdy. of sec. 36.
	Over rolling land, through scattered greasewood and sagebrush.
5.50	Draw, drains S.; asc. 50 ft. over a W. slope.
38.50	Spur, slopes S.
39.92	The standard ¼ sec. cor. of sec. 36, monumented with a granite stone, 18x10x7 ins., mkd. ¼ on N. face, firmly set and exposed 8 ins. above ground, with a mound of stone N. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC TLN R48E <u>¼ S 36</u></p>
	1976
	deposit the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post, and rebuild the mound of stone, 3 ft. high, 2 ft. wide, N. of cor.
	S. 89° 05' E., beginning new measurement.
	Over rolling land; desc. 140 ft. over an E. slope.
12.20	Wash, 8 chs. wide, 10 ft. deep, drains SSW.; asc. 230 ft. over a W. slope.
39.02	Point for the standard cor. of Tps. 1 N., Rs. 48 and 49 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.