

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASE LINE,
THROUGH R. 49 E., MDM, NEVADA

CHAINS	
35.00	Ridge, bears ENE. and WSW.; desc. 20 ft. over an ESE. slope.
40.16	The standard cor. of secs. 35 and 36, monumented with a basalt stone, 17x8x6 ins., mkd. with 5 grooves on W. face and 1 groove on E. face, firmly set in a mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	S C T1N R49E <u>S 35 S 36</u>
	1976
	deposit the original cornerstone and set a steel fence post, 5½ ft. long, 16 ins. in the ground, alongside the iron post.
	S. 88° 31' E., along the S. bdy. of sec. 36.
	Over mountainous land, through medium pinon, juniper, scattered sagebrush and native grasses; desc. 200 ft. over an ESE. slope.
18.00	Draw, drains SE.; asc. 200 ft. over a broken SW. slope.
34.00	Spur, slopes S.; desc. 80 ft. over a NE. slope.
38.95	The standard ¼ sec. cor. of sec. 36, monumented with an unmarked basalt stone, 17x10x8 ins., firmly set and exposed 11 ins. above ground, with a mound of stone N. This is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	S C T1N R49E <u>¼ S 36</u>
	1976
	deposit the unmarked stone and set a steel fence post, 5½ ft. long, 6 ins. in the ground, alongside the iron post.