

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 36 N., R. 34 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 36 N., R. 34 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
H.B. Maxson, U.S. Deputy Surveyor,
in 1888,
and the Partial Retracement Executed by
N.E. Potter, G.L.O. Transitman,
in 1912.

From the standard cor. of Tps. 36 N., Rs. 34 and 35 E.
N. 0° 04' E., bet. secs. 31 and 36.

Over gently rolling land, through shadscale and sage-
brush; asc. 120 ft. over a S. slope to the $\frac{1}{4}$ sec. cor.

10.40 Underground telephone cable, bears ESE. and WNW.

20.90 Graded gravel road, State Route No. 49, bears ESE.
and WNW.

40.66 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a
basalt stone, 14x12x8 ins., plainly mkd. $\frac{1}{4}$ on the W.
face, firmly set and exposed 6 ins. above ground, with
a steel fence post set alongside.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T36N
R34E R35E
 $\frac{1}{4}$
S 36|S 31

1976

bury the original cornerstone and reset the steel fence
post, 6 ft. long, 22 ins. in the ground, alongside the
iron post and raise a mound of stone, 3 $\frac{1}{2}$ ft. base,
2 $\frac{1}{2}$ ft. high, W. of cor.

N. 0° 18' E., beginning new measurement.

Over gently rolling land; asc. 200 ft. over a rolling
S. slope.

20.32 From this point, a basalt stone, 14x12x4 ins., plainly
mkd. with 5 notches on the N. edge and 1 notch on the
S. edge, loosely set alongside a steel fence post,
firmly set and exposed 4 ft. above ground, bears WEST,
0.04 chs. dist. After studying the evidence, this
monument can not be accepted as the position of the
original corner.