

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MDM, NEVADA

CHAINS	
65.00	Ravine, drains SW.; over a S. slope.
74.00	Spur, slopes SW.; desc. 60 ft. over a W. slope.
80.46	The cor. of secs. 29, 30, 31 and 32.
	<hr/>
	N. 89° 43' W., bet. secs. 30 and 31.
	Over mountainous land, through juniper, mahogany, pinon and sagebrush; desc. 220 ft. over a SE. slope.
19.00	Ravine, drains NNW.; asc. 120 ft. to the ¼ sec. cor.
32.00	Trail road, bears NE. and WSW.
40.00	The ¼ sec. cor. of secs. 30 and 31, monumented with a mound of stone. No marked stone found. This is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div>T37N R63E ¼ $\frac{S\ 30}{S\ 31}$ 1977</div>
	raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.
	<hr/>
	S. 89° 06' W., beginning new measurement.
	Over mountainous land; asc. 80 ft. over a NE. slope.
5.00	Spur, slopes N.; desc. 200 ft. over a W. slope.
22.00	Ravine, drains NNE.; asc. 200 ft. over an E. slope.
39.27	Point for the closing cor. of secs. 30 and 31, on the E. bdy. of sec. 36, T. 37 N. R. 62 E., and at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.
	<div>T37N R62E R63E S 36 $\frac{S\ 30}{S\ 31}$CC 1977</div>
	From this corner, the cor. of secs. 25 and 36, T. 37 N., R. 62 E., hereinbefore described, bears N. 0° 01' W., 1.09 chs. dist.
	<hr/>