

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 37 N., R. 63 E., MDM, NEVADA

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 6 ft. base, with brass cap mkd.
	<div style="text-align: center;"> T37N R63E  ¼ <math>\frac{S\ 19}{S\ 30}</math> </div>
	1976
42.00	Spur, slopes SW.; desc. 420 ft. over a W. slope.
60.00	Trail road, bears SSE. and NNW.
61.00	Ravine, drains NNW.; asc. 120 ft. over a NE. slope.
79.12	Point for the closing cor. of secs. 19 and 30, on the E. bdy. of sec. 25, T. 37 N., R. 62 E., and at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T37N  R62E R63E  S 25 <math>\frac{S\ 19}{S\ 30}</math> </div>
	1977
	raise a mound of stone, 3½ ft. base, 2½ ft. high, E. of cor.
	From this corner, the cor. of secs. 24 and 25, T. 37 N., R. 62 E., hereinbefore described, bears N. 0° 05' E., 1.96 chs. dist.
	Point for the W. ¼ sec. cor. of sec. 30, on the E. bdy. of sec. 25, T. 37 N., R. 62 E., and at midpoint bet. the closing cors.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T37N  R62E R63E    ¼    S 30 </div>
	1977
	raise a mound of stone, 3½ ft. base, 2½ ft. high, E. of cor.
	From this corner, the E. ¼ sec. cor. of sec. 25, T. 37 N., R. 62 E., hereinbefore described, bears N. 0° 03' W., 1.51 chs. dist.