

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MDM, NEVADA

CHAINS	
32.00	Ravine, drains NNE.; asc. 20 ft. over an E. slope.
40.19	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ¹ / ₂ ins. long, 2 ¹ / ₂ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T37N R63E $\frac{1}{4} \frac{S \ 17}{S \ 20}$ 1977 </div> raise a mound of stone, 3 ft. base, 2 ¹ / ₂ ft. high, N. of cor.
41.00	Ravine, drains NE.; asc. 60 ft. over an E. slope.
58.00	Trail road, bears N. and S.; asc. 260 ft. over a SE. slope.
80.38	The cor. of secs. 17, 18, 19 and 20. <hr/> S. 88° 17' W., bet. secs. 18 and 19. Over mountainous land, through juniper, pinon and sagebrush; asc. 80 ft. over a SE. slope. 7.00 Spur, slopes NNE.; over a N. slope. 13.00 Spur, slopes NW.; desc. 320 ft. over a W. slope. 40.18 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 ¹ / ₂ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T37N R63E $\frac{1}{4} \frac{S \ 18}{S \ 19}$ 1977 </div> raise a mound of stone, 3 ¹ / ₂ ft. base, 2 ¹ / ₂ ft. high, N. of cor. Desc. 120 ft. over a NW. slope.
49.00	Ravine, drains NNE.; asc. 80 ft. over a NE. slope.
62.00	Spur, slopes N.; desc. 160 ft. over a NW. slope.
79.08	Point for the closing cor. of secs. 18 and 19, on the E. bdy. of sec. 24, T. 37 N., R. 62 E., and at proportionate distance; there is no remaining evidence of the original corner.