

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 37 N., R. 63 E., MDM, NEVADA

CHAINS	
	S. $88^{\circ} 43'$ W., bet. secs. 6 and 7.
	Over gently rolling land, through sagebrush; desc. 40 ft. over a NW. slope to the $\frac{1}{4}$ sec. cor.
2.38	Telephone line, bears ENE. and WSW.
4.63	Southern Pacific railroad tracks, bear ENE. and WSW.
5.48	Southern Pacific railroad tracks, bear ENE. and WSW.
16.40	Fence, parallels railroad tracks.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T37N \ R63E \\ \frac{1}{4} \frac{S \ 6}{S \ 7} \end{array}$
	1976
	raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
78.90	Point for the closing cor. of secs. 6 and 7, on the E. bdy. of sec. 12, T. 37 N., R. 63 E., and at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T37N \\ R62E   R63E \\ S \ 12   \frac{S \ 6}{S \ 7} CC \end{array}$
	1976
	raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, E. of cor.
	From this corner, the cor. of secs. 1 and 12, T. 37 N., R. 62 E., hereinbefore described, bears N. $0^{\circ} 16'$ E., 7.90 chs. dist.; there is no remaining evidence of the original corner.
	Point for the W. $\frac{1}{4}$ sec. cor. of sec. 7, on the E. bdy. of sec. 12, T. 37 N., R. 62 E., and at midpoint bet. the closing cors.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.