RETRACEMENT AND PARTIAL RESURVEY OF THE EAST BOUNDARY,
T. 35 N., R. 64 E., MDM, NEVADA

7		10)/ No 9 It 04 Fier MING NEVADA
	CHAINS	From this same corner, the SW. cor. of sec. 7, T. 35 N., R. 65 E., as resurveyed by Potter, monumented with an iron post, 3 ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 65 E., resurveyed concurrently under this same group, bears N. 89° 35' W., 25.50 chs. dist. Thence N. 0° 53' E., across sec. 7, T. 35 N., R. 65 E., continuing measurement.
	41.40	Point for the k sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. NOT MONUMENTED.
	42.50	Trail road, bears S. 80° E. and N. 80° W.
	82.80	The cor. of secs. 1 and 12, monumented with decayed remains of a wooden post in small pieces, no marks visible, loosely set in a mound of earth. This corner now refers to sec. 1 only.
		At the corner point
		Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
		T35N R64E S 1 R65E S 7
		1976
		deposit the remains of the original wooden post alongside the aluminum post and raise a mound of stone, 2 ft. base, 2 ft. high, NW. of cor.
		N. 17° 35' W., on the E. bdy. of sec. 1.
	,	Over nearly level land, through greasewood.
	2.45	The crossing closing corner of sec. 6, T. 35 N., R. 65 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 35 N., R. 65 E., resurveyed concurrently under this same group.
	43.27	Point for the % sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original corner.
		Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with aluminum cap mkd.
		T35N R64E R65E 戈 S 1
		1976
		raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.