

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 35 N., R. 64 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T35N R64E $\frac{1}{4}$ S 2 S 1</p> <p style="text-align: center;">1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>87.15 Intersect the Seventh Standard Parallel North.</p> <p>Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E S 35 S 2 S 1 T35N R64E CC</p> <p style="text-align: center;">1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 36 N., R. 64 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the Seventh Standard Parallel North, through R. 64 E., resurveyed concurrently under this same group, bears N. $89^{\circ} 59' W.$, 12.61 chs. dist.</p> <hr/> <p>Point for the N. $\frac{1}{4}$ sec. cor. of sec. 1, is on the S. bdy. of sec. 36, T. 36 N., R. 64 E., and at midpoint bet. the closing cors.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E $\frac{1}{4}$ S 1 T35N R64E</p> <p style="text-align: center;">1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the standard cor. of secs. 35 and 36, T. 36 N., R. 64 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of T. 36 N., R. 64 E., resurveyed concurrently under this same group, bears N. $89^{\circ} 47' W.$, 12.37 chs. dist.</p> <hr/>