## DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES T. 35 N., R. 64 E., MDM, NEVADA

|   |          | T. 35 N., R. 64 E., MDM, NEVADA  |
|---|----------|--|
|   | CHAINS   | From the cor. of secs. 1, 2, 11 and 12.  |
|   |          | N. 89° 40' W., bet. secs. 2 and 11.  |
|   |          | Over nearly level land, through greasewood.  |
|   | 10.00    | Fence, bears N. 10° E. and S. 10° W.   |
|   | 40.16    | Point for the 4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner. |
|   | e e      | Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins in the ground, with aluminum cap mkd.                                |
| , |          | T35N R64E<br>4 S 2<br>5 11   |
|   |          | 1976   |
|   |          | raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.   |
|   | 47.50    | Fence, bears N. and S.   |
|   | 80.32    | The cor. of secs. 2, 3, 10 and 11.   |
|   |          | N. 17° 38' W., bet. secs. 2 and 3.   |
|   |          | Over nearly level land, through greasewood.  |
|   | 23.30    | Fence, bears E. and W.   |
|   | 43.11    | Point for the 4 cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.       |
|   |          | Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.                               |
|   |          | T35N R64E<br><sup>1</sup> 4<br>S 3 S 2   |
|   |          | 1976   |
|   | :<br>• . | raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.   |
|   | 61.70    | Enter meadow, edge bears easterly and westerly.  |
|   | 86.76    | Intersect the Seventh Standard Parallel North.   |
|   |          | Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. |
|   |          |  |
|   |          |  |
|   |          |  |
|   |          |  |