

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 35 N., R. 64 E., MDM, NEVADA

CHAINS
86.03

Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins in the ground, with aluminum cap mkd.

T36N R64E
S 33
S 4 | S 3
T35N R64E
CC

1976

set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the aluminum post.

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 36 N., R. 64 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 36 N., R. 64 E., resurveyed concurrently under this same group, bears N. $89^{\circ} 59' W.$, 12.39 chs. dist.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3, is on the S. bdy. of sec. 34, T. 36 N., R. 64 E., and at midpoint bet. the closing cors.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins in the ground, with aluminum cap mkd.

T36N R64E
 $\frac{1}{4}$ S 3
T35N R64E

1976

corner falls on N. edge of pond.

set a steel fence, post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground alongside the aluminum post.

From this cor., the standard cor. of secs. 33 and 34, T. 36 N., R. 64 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, and in a collar of stone, with aluminum cap mkd. as described in the field notes of T. 36 N., R. 64 E., resurveyed concurrently under this same group, bears N. $89^{\circ} 59' W.$, 12.30 chs. dist.