

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES  
T. 35 N., R. 64 E., MDM, NEVADA

CHAINS	
85.53	<p>T35N R64E  <math>\frac{1}{4}</math>  S 5   S 4    1976</p> <p>Intersect the Seventh Standard Parallel North.</p> <p>Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p>T36N R64E  S 32  S 5   S 4  T35N R64E  CC    1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.</p> <p>From this cor., the standard <math>\frac{1}{4}</math> sec. cor. of sec. 32, T. 36 N., R. 64 E., monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set and exposed 24 ins. above ground and in mound of stone, 5 ft. base to top, with aluminum cap mkd. as described in the field notes of T. 36 N., R. 64 E., resurveyed concurrently under this same group, bears N. <math>89^{\circ} 52'</math> W., 12.66 chs. dist.</p> <hr/> <p>Point for the N. <math>\frac{1}{4}</math> sec. cor. of sec. 4, is on the S. bdy. of sec. 33, T. 36 N., R. 64 E., and at midpoint bet. the closing cors.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p>T36N R64E  <math>\frac{1}{4}</math> S 4  T35N R64E    1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.</p> <p>From this cor., the standard cor. of secs. 32 and 33, T. 36 N., R. 64 E., monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set and exposed 6 ins. above ground with aluminum cap mkd. as described in the field notes of T. 36 N., R. 64 E., resurveyed concurrently under this same group, bears N. <math>89^{\circ} 59'</math> W., 12.585 chs. dist.</p>