

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES  
T. 35 N., R. 64 E., MDM, NEVADA

CHAINS	
	S. 83° 50' W., bet. secs. 6 and 7.
	Over nearly level land, through greasewood and scattered pinon.
7.60	Trail road, bears N. and S., also base of hill; asc. over ESE. slope.
22.10	Ridge, bears NW. and SE.; desc. over SW. slope.
40.49	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<p style="text-align: center;">T35N R64E ¼ <math>\frac{S \ 6}{S \ 7}</math></p>
	<p style="text-align: center;">1976</p>
	raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
67.10	Trail road, bears S. 10° E. and N. 10° W.; also ravine, drains SE.; asc. over gentle NW. slope.
78.25	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	<hr/>
	From the cor. of secs. 5, 6, 7 and 8.
	N. 16° 10' W., bet. secs. 5 and 6.
	Over nearly level land, through greasewood.
40.20	Wash, 5 chs. wide, 5 ft. deep, drains ESE.
42.68	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<p style="text-align: center;">T35N R64E ¼ S 6   S 5</p>
	<p style="text-align: center;">1976</p>
	raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
	Ascend over SE. slope.
84.79	Intersect the Seventh Standard Parallel North.