

TOWNSHIP 36 NORTH, RANGE 64 EAST, MDM, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the Seventh Standard Parallel North, through Range 64 E., and the east boundary and the subdivisional lines of Township 36 North, Range 64 East, Mount Diablo Meridian, Nevada.

The exterior boundaries and the subdivisional lines of T. 36 N., R. 64 E. were surveyed by U.S. Deputy Surveyors D.H. Barker and J.H. Eaton, in 1879. The Seventh Standard Parallel North, was resurveyed through R. 65 E., and a portion of R. 64 E., and the east boundary of T. 36 N., R. 64 E. was retraced by Newton E. Potter, U.S. Surveyor, in 1914. The NE. Township corner was remonumented by Newton E. Potter, U.S. Surveyor, in 1914. The west and north boundaries were dependently resurveyed by Cadastral Surveyor Michael R. Collie, under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 22, 1976.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and a diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The direction of lines of this survey were determined by azimuth determined from U.S.G.S. Station "LID". The lines were carried forward by sustained angulation.

The geographic position for the southeast corner of sec. 36, T. 36 N., R. 64 E., determined from U.S.G.S. HLS 42 is:

Latitude: 40° 57' 07" N., Longitude: 114° 40' 38" W.

Mean magnetic declination was found to be 17½° E.

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,
THROUGH RANGE 64 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
U.S. Deputy Surveyors D.H. Barker and J.H. Eaton, in 1879
and the Resurvey of a Portion by Newton E. Potter,
U.S. Surveyor, in 1914.

Beginning at the standard cor. of Tps. 36 N., Rs. 64 and 65 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 11 ins. above ground, with brass cap mkd. as described in the field notes of the resurvey of T. 36 N., R. 65 E., executed under Group No. 26.