

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,
THROUGH RANGE 64 EAST, MDM, NEVADA

CHAINS	
3.70	Graded road, bears N. 15° E. and S. 15° W.
27.25	The closing corner of secs. 4 and 5, T. 35 N., R. 64 E., monumented with an aluminum post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the resurvey of T. 35 N., R. 64 E., executed concurrently under this same group.
39.91	Point for the standard ¼ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 5 ft. base to top, with aluminum cap mkd. <div style="text-align: center;"> SC T36N R64E <u>¼ S 32</u> 1976 </div>
66.00	Spur, slopes N. and S., descend over SW. slope.
67.055	The N. ¼ sec. cor. of sec. 5, T. 35 N., R. 64 E., monumented with an aluminum post, 2½ ins. diam., firmly set in a mound of stone, 5 ft. base, 2 ft. high, with aluminum cap mkd. as described in the field notes of the resurvey of T. 35 N., R. 64 E., executed concurrently under this same group.
69.20	Ravine, drains S.; ascend over SE. slope.
79.82	Point for the standard corner of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. <div style="text-align: center;"> SC T36N R64E <u>S 31 S 32</u> 1976 </div>
	N. 89° 52' W., along the S. bdy. of sec. 31. Ascend over broken SE. slope, through sagebrush and scattered juniper and pinon.
19.60	Spur, slopes SW.; descend over WSW. slope.
24.30	Ravine, drains S.; ascend over SE. slope.