

DEPENDENT RESURVEY OF THE EAST BOUNDARY  
T. 36 N., R. 64 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF THE EAST BOUNDARY OF TOWNSHIP 36 NORTH, RANGE 64 EAST, MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyors D.H. Barker and J.H. Eaton, in 1879, and Retraced by Newton E. Potter, U.S. Surveyor, in 1914.</p> <hr/> <p>From the standard cor. of Tps. 36 N., Rs. 64 and 65 E., on the S. bdy. of the Tp.</p> <p>N. 0° 04' E., bet. secs. 31 and 36.</p> <p>Over nearly level land, through greasewood and sagebrush.</p> <p>38.90 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 36, at propor- tionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E R65E <math>\frac{1}{4}</math> S 36   S 31</p> <p style="text-align: center;">1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>71.00 Trail road bears E. and W.</p> <p>77.80 The cor. of secs. 25, 30, 31 and 36, monumented with a squared wooden post, <math>1\frac{1}{2}</math> x <math>1\frac{1}{2}</math> x 36 ins. long, illegible scribe marks visible, firmly attached to steel pipe, 2 ins. diam., firmly set and exposed 4 ft. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E R65E S 25   S 30 S 36   S 31</p> <p style="text-align: center;">1976</p> <p>deposit the original wooden post and reset steel pipe alongside aluminum post and raise mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>