

DEPENDENT RESURVEY OF THE EAST BOUNDARY
OF T. 36 N., R. 64 E., MDM, NEVADA

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p>T36N R64E R65E ¼ S 12 S 7</p> <p>1976</p> <p>deposit the original wooden post and reset steel fence post alongside aluminum post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr/>
	<p>N. 0° 13' W., beginning new measurement.</p> <p>Over nearly level land.</p>
18.90	Enter corral, fence bears E. and W.
23.10	Leave corral, fence bears E. and W.
40.84	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a steel pipe, 2 ins. diam., firmly set and exposed 4 ft. above ground, with several wooden chips lying loosely around pipe.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p>T36N R64E R65E S 1 S 6 S 12 S 7</p> <p>1976</p> <p>deposit wooden chips and reset steel pipe alongside aluminum post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr/>
	<p>N. 1° 37' W., bet. secs. 1 and 6.</p> <p>Over nearly level land, through greasewood and sagebrush.</p>
38.60	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with a squared wooden post, 2 x 2 x 30 ins. long, no marks visible, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p>T36N R64E R65E ¼ S 1 S 6</p> <p>1976</p> <p>deposit the original wooden post alongside aluminum post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr/>