

DEPENDENT RESURVEY OF THE EAST BOUNDARY
OF T. 36 N., R. 64 E., MDM, NEVADA

CHAINS	
40.74	<p>N. 1° 06' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The corner of Tps. 36 and 37 N., Rs. 64 and 65 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 12 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 65 E., resurveyed under Group No. 26.</p>
	<p>DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF TOWNSHIP 36 NORTH, RANGE 64 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p>
39.27	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyors D.H. Barker and J.H. Eaton, in 1879.</p> <hr/> <p>From the standard corner of secs. 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 32' E., bet. secs. 35 and 36.</p> <p>Over nearly level land, through greasewood and sagebrush.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R65E $\frac{1}{4}$ S 35 S 36 1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>
78.54	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a squared wooden post, 1½ x 1½ x 36 ins. long, with illegible scribe marks visible, firmly attached to steel fence post, firmly set and exposed 4 ft. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E S 26 S 25 S 35 S 36 1976</p> <p>deposit the original wooden post and reset steel fence post alongside aluminum post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>