

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES  
OF T. 36 N., R. 64 E., MDM, NEVADA

CHAINS		
39.69	<p>N. 0° 51' W., bet. secs. 1 and 2.</p> <p>Over nearly level land, through greasewood and sagebrush.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E <math>\frac{1}{4}</math> S 2   S 1  1976</p>	
79.99	<p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>The cor. of secs. 1, 2, 34 and 36, on the N. bdy. of the Tp., monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the resurvey of T. 37 N., R. 64 E., executed concurrently under this same group.</p> <hr/> <p>From the standard corner of secs. 34 and 35, on the S. bdy. of the Tp.</p> <p>N. 0° 12' W., bet. secs. 34 and 35.</p> <p>Over nearly level land, through sagebrush, greasewood and grasses.</p> <p>9.30 Fence, bears S. 70° E. and N. 70° W.</p> <p>39.84 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E <math>\frac{1}{4}</math> S 34   S 35  1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>79.68 The cor. of secs. 26, 27, 34 and 35, monumented with a wooden post, in pieces, 2 ins. diam., 18 ins. long, with illegible scribe marks visible, firmly attached to steel fence post, firmly set and exposed 4 ft. above ground.</p> <p>At the corner point</p>	