

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
OF T. 36 N., R. 64 E., MDM, NEVADA

CHAINS	
39.82	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E $\frac{1}{4}$ S 4 S 3</p> <p style="text-align: center;">1976</p>
80.11	<p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the resurvey of T. 37 N., R. 64 E., executed under this same group.</p> <hr/> <p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 01'$ W., bet. secs. 32 and 33.</p> <p>Ascend over gently rolling land, through sagebrush and greasewood.</p>
13.00	Graded road, bears NNE. and SSW.
21.00	Ravine, drains ENE.
39.89	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R64E $\frac{1}{4}$ S 32 S 33</p> <p style="text-align: center;">1976</p>
46.00	raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
79.78	<p>Ravine, drains ESE.</p> <p>The cor. of secs. 28, 29, 32 and 33, monumented with a limestone, 10 x 8 x 8 ins., plainly mkd. with 4 grooves on E. face and 1 notch on S. edge, firmly set and exposed 6 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>