

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES  
OF T. 36 N., R. 64 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T36N R64E  <math>\frac{1}{4} \frac{S}{S} \frac{4}{9}</math>  1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.</p> <p>71.90 Graded road, bears NNE. and SSW.</p> <p>79.80 The cor. of secs. 4, 5, 8 and 9.</p>
	<p>N. 1° 27' W., bet. secs. 4 and 5.</p> <p>Ascend over gradual SE. slope, through greasewood and sagebrush.</p> <p>39.71 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T36N R64E  <math>\frac{1}{4}</math>  S 5   S 4  1976</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>79.92 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with aluminum cap mkd. as described in the field notes of the resurvey of T. 37 N., R. 64 E., executed concurrently under this same group.</p>
	<p>From the standard corner of secs. 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 16' W., bet. secs. 31 and 32.</p> <p>Ascend over broken SE. slope, through sagebrush and scatterings of juniper and pinon.</p>
	<p>25.30 Spur, slopes ESE.; descend over NE. slope.</p>
	<p>39.79 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.</p>