DEPENDENT RESURVEY OF THE SOUTH BOUNDARY OF T. 37 N., R. 64 E., MDM, NEVADA

	T. 37 N., R. 64 E., MDM, NEVADA
CHAINS 79.00	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.
	T37N R64E <u>S 31 S 32</u> S 6 S 5 T36N
	1976
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor
	S. 89° 37' W., bet. secs. 6 and 31.
	Over rolling land, covered with sagebrush and juniper.
19.00	Spur, slopes N.
39 . 5 0	Point for the 4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.
	T37N R64E ¹ 4 S 31 T36N
	1976
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor
	Asc. over E. slope changing to NE.
79.83	The cor. of Tps. 36 and 37 N., Rs. 63 and 64 E., monumented with an unmarked trachyte stone, 16 x 12 x 8 ins. firmly set in a mound of stone. This is accepted as the best available evidence of the position of the original corner.
	At the corner point.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T37N R63E R64E S 36 S 31 S 1 S 6 T36N
	1976
	deposit the unmarked stone alongside the iron post in the mound of stone.