

TOWNSHIP 35 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey by U.S. Deputy Surveyors, J.H. Eaton and D.H. Barker, in 1879 and the Resurvey executed by Newton E. Potter, in 1914.

Beginning at the standard cor. of secs. 31 and 32, T. 36 N., R. 65 E., monumented with iron post, 3 ins. diam., firmly set and exposed 9 ins. above ground, with brass cap mkd. as described in the field notes of the resurvey of T. 36 N., R. 65 E., executed under Group No. 26.

S. 89° 59' W., along the S. bdy. of sec. 31.

Over nearly level land, through greasewood.

33.31 The closing cor. of secs. 5 and 6, T. 35 N., R. 65 E., hereinafter described.

39.91 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance. The 1914 iron post, 30 ins. long, 1 in. diam., with brass cap mkd. as described in the field notes of T. 36 N., R. 65 E., executed under Group No. 26, was found about 10 feet S., bent and lying on top of the ground.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SC
T36N R65E
 $\frac{1}{4}$ S 31

1976

deposit 1 in. iron post alongside aluminum post and set a steel fence post, $5\frac{1}{2}$ ft. long, 2 ft. in the ground, alongside the aluminum post.

73.31 The N. $\frac{1}{4}$ sec. cor. of sec. 6, T. 35 N., R. 65 E., hereinafter described.

79.82 The standard cor. of Tps. 36 N., Rs. 64 and 65 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 11 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 65 E., executed under Group No. 26.