CHAINS

RETRACEMENT AND PARTIAL REESTABLISHMENT OF THE
WEST BOUNDARY, T. 35 N., R. 65 E.,
MOUNT DIABLO MERIDIAN, NEVADA

Retracement and Partial Reestablishment of the Survey
Executed by Newton E. Potter, U.S. Surveyor, in 1914.

From the SW. cor. of sec. 31, T. 35 N., R. 65 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 65 E., executed under Group No. 522.

N. 0° 01' E., on the W. bdy. of sec. 31.

Over nearly level land, through greasewood.

25.82 The E. ¼ sec. cor. of sec. 36, T. 35 N., R. 64 E., monumented with an aluminum post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of T. 35 N., R. 64 E., resurveyed concurrently under this same group.

40.00 The ¼ sec. cor. of secs. 31 and 36, as resurveyed by Potter, monumented with an iron post, 1 in. diam., rusted off at ground level, with brass cap lying alongside, mkd. as described in the field notes of T. 35 N., R. 65 E., executed under Group No. 26. This corner now refers to sec. 31 only.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T35N
R64E R65E
| ¼
|S 31

1976

deposit the original iron post alongside the aluminum post, and raise mound of stone, 2 ft. base, 2 ft. high, E. of cor.

N. 0° 04' E., beginning new measurement.

Over nearly level land.

26.96 The crossing closing cor. of sec. 36, T. 35 N., R. 64 E., monumented with an aluminum post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of T. 35 N., R. 64 E., resurveyed concurrently under this same group.