

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 35 N., R. 65 E., MDM, NEVADA

CHAINS		
	<p>From this corner, the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., as resurveyed by Potter and now an AM, bears N. <math>89^{\circ} 36'</math> W., 13.18 chs. dist.</p> <p>From this same corner, the <math>\frac{1}{4}</math> sec. cor. of sec. 1, T. 35 N., R. 64 E., monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam. firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the resurvey of the E. bdy. of T. 35 N., R. 64 E., executed concurrently under this same group, bears S. <math>17^{\circ} 35'</math> E., 1.22 chs. dist.</p> <p>From this same corner, the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6, bears S. <math>89^{\circ} 36'</math> E.</p>	
39.96	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. <math>0^{\circ} 04'</math> W., bet. secs. 5 and 6.</p> <p>Over nearly level land, through greasewood.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set and exposed 8 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 65 E., executed under group No. 26. The brass cap is remarked.</p> <p style="text-align: center;">T35N R65E <math>\frac{1}{4}</math> S 6   S 5</p> <p style="text-align: center;">1976 1914</p>	
42.26	<p>N. <math>0^{\circ} 04'</math> W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>Intersect the Seventh Standard Parallel North.</p> <p>The closing cor. of secs. 5 and 6, monumented with an iron post, 3 ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 65 E., executed under Group No. 26.</p> <p>From this cor., the standard <math>\frac{1}{4}</math> sec. cor. of sec. 31, T. 36 N., R. 65 E., bears S. <math>89^{\circ} 59'</math> W., 6.60 chs. dist.</p> <p>Point for the N. <math>\frac{1}{4}</math> sec. cor. of sec. 6, at proportionate distance, and on the S. bdy. of sec. 31, T. 36 N., R. 65 E.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R65E <math>\frac{1}{4}</math> S 6 T35N R65E</p> <p style="text-align: center;">1976</p> <p>set a steel fence post, <math>5\frac{1}{2}</math> ft. long, 2 ft. in the ground, alongside aluminum post.</p>	