

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
T. 29 N., R. 64 E., MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T29N R64E} \\ \text{S 31   S 32} \\ \hline \text{S 6   S 5} \\ \text{T28N} \end{array}$ <p>1976</p> <p>reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>S. 89° 09' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land, through scattered sagebrush.</p> <p>4.70 Fence, parallels highway.</p> <p>6.40 U.S. Highway No. 93, bears N. 22¼° W. and S. 22¼° E.</p> <p>8.00 Fence, parallels highway.</p> <p>39.88 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T29N R64E} \\ \frac{1}{4} \frac{\text{S 31}}{\text{S 6}} \\ \text{T28N} \end{array}$ <p>1976</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
78.72	<p>The original cor. of Tps. 28 and 29 N., Rs. 63 and 64 E., monumented with the decayed remains of a squared willow post, 14 ins. long, ½ in. square firmly set and exposed 10 ins. above ground with illegible scribe marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T29N} \\ \text{R63E R64E} \\ \text{S 36   S 31} \\ \hline \text{S 1   S 6} \\ \text{T28N} \end{array}$ <p>1976</p> <p>reset the wooden post alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.</p>