Dependent Resurvey, Portion of East Boundary, T. 32 N., R. 44 E., Mount Diablo Mer., Nevada

CHAINS 40.00

The cor. of secs. 1, 6, 7, and 12, perpetuated by Mark Chilton, R.P.L.S. 1404, in 1975, as shown on the plat of survey recorded in Lander Co.; monumented with the rotted remains of a willow post,  $12 \times 4 \times 2\frac{1}{2}$  ins., with no visible marks, attached to a steel fence post, firmly set in the ground; this point is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 N

S 1 | S 6 S 12 | S 7

R 44 E R 45 E

1976

Set the willow post and steel fence post alongside the cor.

Dependent Resurvey of a Portion of the Subdivisional Lines T. 32 N., R. 44 E., Mount Diablo Meridian, Nevada

(Restoring the 1869 survey by Hatch and Eaton)

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the tp.

S. 89° 56' W., bet. secs. 12 and 13.

Over level land, along a gravel road, within the right-of-way of Interstate Highway No. 80.

- Point in line with fences to the N. and S., leave the right-of-way of Interstate Highway No. 80.
- 20.38 | Point for the E. 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. below surface of the grayel road, with brass cap mkd.

T 32 N R 44 E

 $E 1/16 \frac{S 12}{S 13}$ 

1976

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 22 ins. in the ground, for a reference monument, bears North, 37.9 lks. dist., with brass cap mkd. E 1/16 S12 RM 25 FT TO COR 1976 and an arrow pointing to the cor.

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 22 ins. in the ground, for a reference monument, bears South, 37.9 lks. dist., with brass cap mkd. E 1/16 S13 RM 25 FT TO COR 1976 and an arrow pointing to the cor.