

Dependent Resurvey, Portion, Subdivisional Lines,
T. 30 N., R. 58 E., Mt. Diablo Mer., Nevada

CHAINS		
	<p>With a mound of stone, 3 ft. base, 1½ ft. high, 5 lks. N. of the cor.</p>	
	<p>Add the marks T30N R58E on the brass cap.</p>	
	<p>S. 88° 41' W., beginning new measurement.</p>	
0.70	<p>The ¼ sec. cor. of sec. 25 only, monumented with an iron post, 1 in. diam., firmly set, protruding 10 ins. above the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">¼ S 25 1924</p>	
	<p>With a mound of stone, 4 ft. base, 1 ft. high, 4 lks. S. of the cor.</p>	
	<p>Add the marks T30N R58E on the brass cap.</p>	
	<p>S. 89° 55' W., beginning new measurement.</p>	
	<p>Asc. over E. slope, through dense sagebrush.</p>	
7.60	<p>Barbed wire fence, 4 strands, extending N. and S.</p>	
19.92	<p>Point for the W. 1/16 sec. cor. of sec. 25 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">W 1/16 S 25 1976</p>	
	<p>Set a steel fence post alongside the iron post.</p>	
30.10	<p>Spur ridge, slopes S.; desc. along SE. slope.</p>	
39.225	<p>The cor. of secs. 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, protruding 13 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T 30 N R 58 E S 23 S 24 1924</p>	
	<p>With a wood post, 4 ins. sq., protruding 5 ft. above the ground, 6 lks. N. of the cor.</p>	
	<p>N. 89° 55' W., bet. secs. 23 and 25.</p>	
0.615	<p>The cor. of secs. 25 and 26.</p>	
	<p style="text-align: center;">Subdivision of Section 24, T. 30 N., R. 58 E., Mount Diablo Meridian, Nevada</p>	
	<p>From the ¼ sec. cor. of sec. 24 only.</p>	
	<p>N. 0° 06' W., on the N. and S. center line of sec. 24.</p>	