CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of secs. 11 and 14, Township 32 North, Range 59 East, Mount Diablo Meridian, Nevada.

A portion of the subdivisional lines were surveyed by Hatch and Eaton, U.S. Deputy Surveyors, in 1869 and 1870, as shown on the official plat of survey approved March 29, 1870. A portion of the subdivisional lines were dependently resurveyed and surveyed, under Group No. 29, by Thomas A. Haigh, U.S. Surveyor, and J.C. Clark, U.S. Transitman, in 1916 and 1917, as shown on the official plat of survey approved April 29, 1919. A portion of the subdivisional lines were retraced, dependently resurveyed and surveyed, under Group No. 138, by Andrew Nelson, U.S. Cadastral Engineer, in 1927, as shown on the official plat of survey accepted December 18, 1930.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 536, Nevada, dated March 30, 1976.

The directions of the lines of this survey were determined by altitude observations on the sun. They refer to the true meridian.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the cor. of secs. 13, 14, 23, and 24, as scaled from the 1962, U.S.G.S. 15 minute series "LAMOILLE, NEVADA", quadrangle map is:

Latitude 40° 38.8' N. Longitude 115° 16.5' W.

The mean magnetic declination is 17½° E.

Dependent Resurvey of a Portion of the Subdivisional Lines T. 32 N., R. 59 E., Mount Diablo Meridian, Nevada

(Restoring the 1869-1870 survey by Hatch and Eaton, the 1916-1917 resurvey by James A. Haigh and J.C. Clark, and the 1927 retracement and resurvey by Andrew Nelson)

Beginning at the cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., protruding 12 ins. above the ground, in a collar of stone, $2\frac{1}{2}$ ft. base, 6 ins. high, with brass cap mkd.

With aluminum fence post alongside the iron post.

N. 0° 17' E., bet. secs. 13 and 14.